

# MULTI-TOUCH G4 Integration Kit



## Highlights

- Reliable performance
- Low cost solution for OEM
- Optimized for integration

## PQ Labs Multi-Touch G4 Integration Kit

PQ Labs multi-touch overlay is plug-and-play solution for both developers and end-users. Exceptional durability and accuracy.

## ■ SPECIFICATION - PART 1

<p><b>Available Sizes</b></p>	<p>32", 40", 42", 46", 47", 50", 52", 55", 60", 65", 70", 80", 84"  <i>Customized sizes available upon request</i></p> <ul style="list-style-type: none"> <li>● Two Sizes of 55"                      Diagonal: 54.6", most LCD TVs                      Diagonal: 55", for Plasma</li> <li>● Two Sizes of 70"                      Diagonal: 69.59", most 70" TVs                      Diagonal: 70.25", Samsung 70" only</li> </ul>
<p><b>Frame Thickness</b></p>	<p>8.6 mm</p>
<p><b>Glass</b></p>	<ul style="list-style-type: none"> <li>● Optional</li> <li>● PQ Labs patented ultra-smooth technology</li> <li>● Glass Thickness                             <ul style="list-style-type: none"> <li>32" – 47": 3 mm Mighty Glass</li> <li>50" – 84": 4 mm Mighty Glass</li> </ul> </li> </ul>
<p><b>Detectable Touch Points</b></p>	<p>True Multi-Touch (Detects over 32 touch points <b>simultaneously</b>)</p> <ul style="list-style-type: none"> <li>● G4 Kit Plus: 32+(unlimited) Touch Points</li> <li>● G4 Kit Standard: 12 Touch Points</li> <li>● G4 Kit Basic: 6 Touch Points</li> <li>● G4 Kit Dual: 2 Touch Points</li> </ul>
<p><b>Operating System</b></p>	<ul style="list-style-type: none"> <li>● Windows 8/7/Vista/XP, Mac OS X, Ubuntu/Fedora</li> <li>● Android (Fully support iStick, other Android devices need to be customized)</li> </ul>
<p><b>Sample Rate</b></p>	<p>Up to 200 fps (depends on frame size)</p>
<p><b>Finger Touch Accuracy</b></p>	<p>2.7 mm</p>

## ■ SPECIFICATION - PART 2

<b>Report Resolution</b>	32768 x 32768
<b>Waterproof</b>	Not available
<b>Assembly Method</b>	Flexible Flat Cable connection
<b>Power Supply</b>	Output: 5V / 4A Power Adaptor
<b>Data Interface</b>	<ul style="list-style-type: none"><li>● USB 2.0 (Full speed), compatible with USB 1.1 port, HID compliant, plug-and-play compatible</li><li>● USB A Type Plug</li></ul>
<b>Touch Method</b>	<ul style="list-style-type: none"><li>● Finger, gloved hand or any other pointer</li><li>● Object shape recognition (Palm, fist recognitions)</li></ul>
<b>Touch Activation Force</b>	No pressure required
<b>Touch Durability</b>	Unlimited
<b>Environment</b>	<ul style="list-style-type: none"><li>● Operating temperature: 0 °C to 55 °C</li><li>● Storage temperature: -25 °C to 85 °C</li><li>● Operating humidity: 10% to 90% RH, non-condensing</li><li>● Storage humidity: 10% to 90% RH, non-condensing</li></ul>